

## TITAN™ SHOCK-ABSORBING LANYARD

- Material: Polyester
- Shock Absorber Type: Pack
- Colour: Orange
- CSA Minimum Mass: 120 lbs.
- CSA Maximum Mass: 335 lbs.
- Certification(s): CSA Standard Z259.11

**Honeywell**  
**MILLER**



| Model No. | Mfg. No.    | Length' | No. of Legs | Harness Connection | Anchorage Connection | Price /Each |
|-----------|-------------|---------|-------------|--------------------|----------------------|-------------|
| SGT479    | T1SSSR-054C | 4       | One         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT473    | T1SSSR-056C | 6       | One         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT487    | T1SSSS-053C | 3       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT474    | T1SSSS-054C | 4       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT472    | T1SSSS-056C | 6       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT494    | T2SSSR-056C | 6       | Two         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT484    | T2SSSS-056C | 6       | Two         | Locking Snap Hook  | Locking Snap Hook    |             |

## MILLER® HP™ LANYARD WITH SOFSTOP® SHOCK ABSORBER

- Features a heavy-duty back-up safety strap
- SofStop® Energy Absorber pack is designed with a specially-woven inner core that smoothly expands to reduce fall arrest forces
- Connectors' Gate Load Capacity: 3600 lbs.
- Material: Polyester
- Shock Absorber Type: Pack
- Colour: Green
- CSA Minimum Mass: 120 lbs.
- CSA Maximum Mass: 335 lbs.
- Certification(s): CSA Standard Z259.11

**Honeywell**  
**MILLER**



| Model No. | Mfg. No.    | Length' | No. of Legs | Harness Connection | Anchorage Connection | Price /Each |
|-----------|-------------|---------|-------------|--------------------|----------------------|-------------|
| SGT535    | M1FSFC-WS4C | 4       | One         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT499    | M1FSFC-WS6C | 6       | One         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT482    | M1FSFR-WS4C | 4       | One         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT486    | M1FSFR-WS6C | 6       | One         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT492    | M1FSFS-WS4C | 4       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT476    | M1FSFS-WS6C | 6       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT507    | M2FSFC-WS4C | 4       | Two         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT520    | M2FSFC-WS6C | 6       | Two         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT485    | M2FSFR-WS4C | 4       | Two         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT511    | M2FSFR-WS6C | 6       | Two         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT496    | M2FSFS-WS4C | 4       | Two         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT510    | M2FSFS-WS6C | 6       | Two         | Locking Snap Hook  | Locking Snap Hook    |             |

## MILLER® BACKBITER® TIE-BACK LANYARD

- All-in-one lanyard with SofStop® Energy Absorber and cross-arm anchorage connector
- SofStop® Energy Absorber pack is designed with a specially-woven inner core that smoothly expands to reduce fall arrest forces
- Heavy-duty polyester webbing and Cordura® nylon webbing with increased abrasion resistance
- Designed from top to bottom for tie-back use with the anchorage connector Miller 5K® Snap Hook
- Harness Connector Gate Load Capacity: 3600 lbs.
- Anchorage Connector Gate Load Capacity: 5000 lbs.
- Material: Nylon, Polyester
- Shock Absorber Type: Pack
- Colour: Green
- CSA Minimum Mass: 120 lbs.
- CSA Maximum Mass: 335 lbs.
- Certification(s): CSA Standard Z259.11

**Honeywell**  
**MILLER**



| Model No. | Mfg. No.    | Length' | No. of Legs | Harness Connection | Anchorage Connection | Price /Each |
|-----------|-------------|---------|-------------|--------------------|----------------------|-------------|
| SGT475    | M1FSTB-AS6C | 6       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT547    | M2FSTB-AS6C | 6       | Two         | Locking Snap Hook  | Locking Snap Hook    |             |

## TITAN™ STRETCH SHOCK-ABSORBING LANYARD

- Material: Polyester
- Shock Absorber Type: Pack
- Colour: Orange
- CSA Minimum Mass: 120 lbs.
- CSA Maximum Mass: 335 lbs.
- Certification(s): CSA Standard Z259.11

**Honeywell**  
**MILLER**



| Model No. | Mfg. No.    | Length' | No. of Legs | Harness Connection | Anchorage Connection | Price /Each |
|-----------|-------------|---------|-------------|--------------------|----------------------|-------------|
| SGT532    | T1SSSS-US6C | 6       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT518    | T2SSSR-US6C | 6       | Two         | Locking Snap Hook  | Locking Rebar Hook   |             |

## MILLER® STRETCHSTOP® LANYARD WITH SOFSTOP® SHOCK ABSORBER

- Features a heavy-duty back-up safety strap
- SofStop® Energy Absorber pack is designed with a specially-woven inner core that smoothly expands to reduce fall arrest forces
- Contracts from 6' (1.8 m) to 4' (1.2 m), greatly reducing the chances of tripping, snagging, or dragging
- Connectors' Gate Load Capacity: 3600 lbs.
- Material: Polyester
- Shock Absorber Type: Pack
- Colour: Green
- CSA Minimum Mass: 120 lbs.
- CSA Maximum Mass: 335 lbs.
- Certification(s): CSA Standard Z259.11

**Honeywell**  
**MILLER**



| Model No. | Mfg. No.    | Length' | No. of Legs | Harness Connection | Anchorage Connection | Price /Each |
|-----------|-------------|---------|-------------|--------------------|----------------------|-------------|
| SGT534    | M1FSFC-TS4C | 4       | One         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT490    | M1FSFC-TS6C | 6       | One         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT480    | M1FSFR-TS4C | 4       | One         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT478    | M1FSFR-TS6C | 6       | One         | Locking Snap Hook  | Locking Rebar Hook   |             |
| SGT483    | M1FSFS-TS4C | 4       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT509    | M1FSFS-TS5C | 5       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT477    | M1FSFS-TS6C | 6       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT501    | M2FSFC-TS4C | 4       | Two         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT515    | M2FSFC-TS6C | 6       | Two         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT491    | M2FSFS-TS6C | 6       | Two         | Locking Snap Hook  | Locking Snap Hook    |             |

## MILLER® VINYL-COATED SHOCK-ABSORBING LANYARD

- Features a special vinyl coating on the webbing to protect against a variety of liquids that could compromise overall performance
- SofStop® Energy Absorber pack is designed with a specially-woven inner core that smoothly expands to reduce fall arrest forces
- Features a heavy-duty back-up safety strap
- Effective in a wide range of applications, including food processing, petrochemical, water treatment, painting, billboards, and general industry
- Material: Polyester
- Shock Absorber Type: Pack
- Colour: Green
- CSA Minimum Mass: 120 lbs.
- CSA Maximum Mass: 335 lbs.
- Certification(s): CSA Standard Z259.11

**Honeywell**  
**MILLER**



| Model No. | Mfg. No.    | Length' | No. of Legs | Harness Connection | Anchorage Connection | Price /Each |
|-----------|-------------|---------|-------------|--------------------|----------------------|-------------|
| SGT538    | M2FSFC-DS6C | 6       | Two         | Locking Snap Hook  | Scaffold Hook        |             |
| SGT488    | M1FSFS-DS6C | 6       | One         | Locking Snap Hook  | Locking Snap Hook    |             |
| SGT517    | M2FSFS-DS6C | 6       | Two         | Locking Snap Hook  | Locking Snap Hook    |             |